

4. ダンプトラック

(1)リジッドフレーム型

型式	排出ガス	低騒音	最大積載量	機械質量	状況	車両総質量	軸	軸量	1輪当たり				寸法			荷台		最小回転半径前輪跡	最高速度	出力	タイヤサイズ	燃料タンク容量
									荷重	接地面積	接地圧	空気圧	全長	全幅	全高	山積容量	積込高さ					
			t	t				kg	kg	kg	cm <sup>2</sup>	kPa	kPa	m	m	m	m <sup>3</sup>					
HD255-5	少特	対象外	25	23.03	空	23,030	前	11,055	5,510	1,270	426	686	7.39	3.2	3.795	17.7	2.975	7	47.5	235.0	16.00R25	374
								後	11,975	2,983	820	357										
					積	48,105	前	15,395	7,697	1,520	496	686										
								後	32,710	8,177	1,575	508										
HD325-7	特特07	対象外	36.5	32.7	空	32,700	前	16,940	8,470	1,580	526	564	8.465	3.66	4.15	24	3.22	7.2	70	371.0	18.00-33-32PR	500
								後	15,760	3,940	900	430										
					積	69,280	前	22,000	11,000	1,860	580	564										
								後	47,280	11,820	1,880	617										
HD405-7	特特07	対象外	40	35	空	35,000	前	17,885	8,943	1,920	457	686	8.465	3.66	4.15	27.3	3.45	7.2	70	371.0	18.00 R33	500
								後	17,115	4,279	1,260	333										
					積	75,080	前	24,850	12,425	2,350	514	686										
								後	50,230	12,558	2,455	502										
HD465-7E0	特特07	対象外	55	44.6	空	44,600	前	20,960	10,480	2,610	394	466	9.355	4.595	4.4	34.2	3.6	8.5	70	533.0	24.00-35-36PR	791
								後	23,640	5,910	1,810	321										
					積	99,680	前	31,900	14,510	3,250	437	466										
								後	67,780	15,415	3,340	453										
HD605-7E0	特特07	対象外	63	47.1	空	47,100	前	22,140	11,070	2,210	491	686	9.355	4.595	4.4	40	3.86	8.5	70	533.0	24.00-R35	791
								後	24,960	6,240	1,500	408										
					積	110,180	前	35,260	17,630	3,050	567	686										
								後	74,920	18,730	3,080	596										
HD785-7	対象外	対象外	91	72.3	空	72,300	前	33,980	16,990	3,391	491	686	10.29	6.885	5.05	60	4.285	10.1	65	895.0	27.00-R49	1,396
								後	38,320	9,580	2,359	398										
					積	163,380	前	61,440	25,733	4,506	560	686										
								後	111,860	27,979	4,775	575										

## (2)アーティキュレート型

型式	排出ガス	低騒音	最大積載量	機械質量	状況	車両総質量	軸	軸量	1輪当たり				寸法			荷台		最小回転半径前輪跡	最高速度	出力	タイヤサイズ	燃料タンク容量		
			t	t					kg	kg	kg	cm <sup>2</sup>	kPa	kPa	m	m	m					m <sup>3</sup>	m	ℓ
HM300-2	特特07	対象外	27.3	24.62	空	24,620		前	13,650	6,825	2,420	279	343	10.44	3.2	3.505	16.6	2.79	8.11	58.1	254.0	750/65R25	384	
								後前	5,850	2,925	1,160	252	402											
								後後	5,120	2,560	1,070	239	402											
					積	52,000		前	15,850	7,980	2,650	295	343											
								後前	18,440	9,220	2,650	245	402											
								後後	17,710	8,855	2,640	331	402											
HM350-2	特特07	対象外	32.3	31.2	空	31,200		前	17,920	8,960	2,370	371	441	11.145	3.25	3.7	19.8	2.975	8.6	57.1	304.0	26.5 R25	500	
								後前	6,730	3,365	1,075	307	441											
								後後	6,550	3,275	1,030	312	441											
					積	63,580		前	20,280	10,140	2,560	388	441											
								後前	21,740	10,870	2,620	407	441											
								後後	21,560	10,780	2,580	410	441											
HM400-2	特特07	対象外	36.5	32.59	空	32,590		前	17,960	8,980	3,093	284	373	11.31	3.45	3.72	22.3	2.97	8.7	58.5	337.0	29.5 R25	500	
								後前	7,440	3,720	1,360	269	373											
								後後	7,190	3,595	1,330	265	373											
					積	69,170		前	20,080	10,040	3,360	293	373											
								後前	24,670	12,335	3,940	307	373											
								後後	24,420	12,210	3,840	312	373											